

YT-H3002 1,3M IPC



- Max resolution can reach 1.3M(1280*960)
- Low illumination,0.1Lux @ (F1.2,AGC ON),0 LUX with IR
- Support IR-CUT filter switch to achieve day and night monitoring
- Support local BNC output
- H.264 High profile compression, achieve low bit-rate, high definition image quality
- Support dual stream
- Support mobile monitor (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support Auto-iris and electronic shutter, adjust for different surveillance environment
- Provide web, CMS, center manage software (MYEYE), and SDK for development
- Support connection with HVR/NVR&Onvif
- Accord with IP66 waterproof design

Model	YT-H3002 1.3Megapixel
Camera	
Image Sensor	1/3" Aptina Low Illumination CMOS Sensor
Low Illumination	Color 0.1Lux @(F1.2,AGC ON),0 LUX with IR BW 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR
Electronic shutter	1/50(1/60)S-1/100,000S
Lens	6mm @F1.8(8mm,12mm optional)
Lens Mount	CS
Day/Night	Support IR-CUT
Compression Standard	
Video Compression	H.264 HighProfile, JPEG snapshot
Bite Rate	100 Kbps~6Mbps
Image	
Max.Image Resolution	1280*960
Frame Rate	50Hz:25fps (1280*720) ,22fps (1280*960) 60Hz: 25fps (1280*720) ,22fps (1280*960)
Network	

Storage	Network storage
Intelligent Alarm	Motion detect,video loss,network disconnection..
Protocol: TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,Ipv6 optional)	
Basic	Anti-flicker,dual stream,heartbeat,password protection
Interface	
Net Interface	1 * RJ45 10M/100M
Video output	1Vp-p Composite Output(75Ω/BNC)
General	
Operating Condition	-10°C~60°C , Humidity 90% or less(non-condensing)
Power supply	DC12V±10%
ProtectionRange	IP66
IR Distance	40M
Dimension	160mm*84mm*69.5mm
Weight	500g